



TAG NO.	Set press.
0127SV001	16Barg
0127SV002	
0127SV007	15Barg

Project		Client			
TAG NO.	Q.T.Y	Nominal Pres.	Nominal Dim.	Set Pres.(Barg)	Weight (Kg)
		300LB	8T10		
Suitable Medium		Medium State		Suitable Temperature(°C)	
Saturated Steam		Vapour		250	
Compliance with technical specifications					
Product design standards	API 520 ASME				
Test standard	API 527				
Centre to Face	API 526				
Thread standard	ASME B16.5				
End connection	Flange				
Flange pressure class	300LB/150LB				
Other					

15	Bolt	ASTM A193 B7			
14	Gasket	Non-Asbestos	29	Locking nut	ASTM A29 1045
13	Guide sleeve	ASTM A351 CF3M	28	Cap	ASTM A216 WCB
12	Filling block	ASTM A182 F316L	27	Adjusting bolt	ASTM A29 1035
11	Disc holder	ASTM A351 CF3M	26	Bearing	
10	Jump ring		25	Pulling yoke	ASTM A216 WCB
9	Disc	ASTM A182 F316L	24	Lever	ASTM A216 WCB
8	Adjusting ring	ASTM A351 CF3M	23	Spring washer	ASTM A29 1035
7	Adjusting ring bolt	ASTM A29 1035	22	Rivet	ML2
6	Nut	ASTM A29 1035	21	Nameplate	L3
5	Body	ASTM A216 WCB	20	Spring	Alloy Steel
4	Plug	ASTM A29 1025	19	Bannet	ASTM A216 WCB
3	Plug Gasket	Brass	18	Washer cushion	ASTM A182 F304
2	Nozzle	ASTM A276 316L	17	Stem	ASTM A182 F316L
1	Gasket	Non-Asbestos	16	Nut	ASTM A194 2H
No.	Parts	Materials	No.	Parts	Materials



THE BEST SOLUTION TO YOUR CORROSIVE PROBLEMS

1601, Autoroute #90,
Suite 2105, Chamblay,
Local Quebec, H5L 1W3,
CANADA

Any Copy, Reproduction Or Translation Of This
Information Either Whole Or In Part, Without
The Express Written Agreement Of VALVTEC
Canada Is Expressly Forbidden

**FULL LIFT SPRING LOADED
STEAM SAFETY VALVE**

TYPE

VCA48C-300LB 8T10